

Biegegeräte mit aufklappbarem Flügelkopf

- Bietet den zusätzlichen Vorteil höherer Steifigkeit beim Biegevorgang.
- Ideal für Anwendungen vor Ort.



Modell HB382E



Best.-Nr.	Modell	Kapazität Zoll	Pumpen- leistung kN	Volt	Motor	Kw	Biegesegmente (Zoll)										Gewicht	
							3⁄8	1⁄2	3⁄4	1	1¼	1½	2	2½	3	4	lb.	kg
Manuell																		
40383	HB382	¾ - 1¼	90	-		-	•	•	•	•	•	-	-	-	-	-	134.5	61
36518	HB382	¾ - 2	90	-		-	•	•	•	•	•	•	-	-	-	-	158.7	72
36523	HB383	¾ - 3	146	-		-	•	•	•	•	•	•	•	•	-	-	344.0	156
14921	3814	¾ - 4	200	-		-	-	-	-	-	-	-	•	•	•	-	904.0	410
27911	3814	¾ - 4	200	-		-	•	•	•	•	•	•	•	•	•	-	926.0	420
Elektrohydraulisch																		
14871	3812E	¾ - 2	80	115	1 PH	1,4	•	•	•	•	•	•	-	-	-	-	220.4	100
39243	HB382E	¾ - 2	90	230	1 PH	1,4	•	•	•	•	•	•	-	-	-	-	211.6	96
13771	3812E	¾ - 2	80	400	3 PH	1,5	•	•	•	•	•	•	-	-	-	-	220.4	100
14881	3813E	¾ - 3	130	115	1 PH	1,4	•	•	•	•	•	•	•	•	-	-	458.5	208
39268	HB383E	¾ - 3	146	230	1 PH	1,4	•	•	•	•	•	•	•	•	-	-	401.2	182
13781	3813E	¾ - 3	130	400	3 PH	1,5	•	•	•	•	•	•	•	•	-	-	458.5	208
14931	3814E	¾ - 4	200	230	1 PH	1,4	-	-	-	-	-	-	-	•	•	•	970.0	440
14941	3814E	¾ - 4	200	400	3 PH	1,5	-	-	-	-	-	-	-	•	•	•	970.0	440

Biegegerät mit verstellbarem Flügelkopf

Zum Herstellen mehrerer Biegungen in verschiedenen Winkeln.



Modell 3812S

Best.-Nr.	Modell	Kapazität Zoll	Pumpenleistung kN	Biegesegmente (Zoll)										Gewicht	
				3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	lb.	kg
16401	3811S	3/8 - 1 1/4	50	•	•	•	•	•	-	-	-	-	-	101.4	46
16411	3812S	3/8 - 2	80	•	•	•	•	•	•	•	-	-	-	176.3	80